

# GENIEMAT® FAS

## FLOORING ADHESIVE SYSTEM



### PRODUCT SPECIFICATION

**PRODUCT NAME:** GenieMat FAS

**DESCRIPTION:** **GenieMat FAS** is a single component 100% solids, cross-linking, polymer-based adhesive formulated for interior installation of all thicknesses of solid/engineered wood, pre-finished and unfinished wood, bamboo and dry-back wood parquet flooring. **GenieMat FAS** also has superior concrete moisture inhibition capability (becoming waterproof when fully cured) and provides isolation for cracks up to 1/8" wide.

This specially formulated adhesive has good early strength buildup for immediate grab and gradually builds into a tenacious but resilient bond as the chemicals in the adhesive cross-link.

**APPLICATION:** **GenieMat FAS** is used for bonding **GenieMat** sound control underlayments to various subfloors/substrates, and for bonding specified wood finish floors to GenieMat™ sound control underlayments.

**INSTALLATION METHOD:** Immediate wet set installation. 60 minute working time. Use a 100 lb roller and allow 16 hours before light traffic, 24 hours before heavy traffic and 72 hours before sanding.

**BASE:** Polymer-Resin Blend

**APPEARANCE:** Off white, smooth, easy-to-spread mastic

**WORKING TIME:** Approximately 60 minutes, depending on temperature and humidity

**SHELF LIFE:** 1 year in unopened container at 21°C (70°F)

## CONTACT Us

For Your Project Specific Questions

**Middle East** +971 4 813 5501 | **UK** +44 203 9846444 | **Asia Pacific** +65 8452 6865

**E.** [info@pliteq.ae](mailto:info@pliteq.ae)

© Pliteq Building Materials Trading LLC. 2020.

®™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



[www.pliteq.ae](http://www.pliteq.ae)

# GENIEMAT® FAS

## FLOORING ADHESIVE SYSTEM



### PRODUCT SPECIFICATION CONTINUED

#### TROWEL SELECTION AND COVERAGE:

\*Trowel dimension is width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and angle at which the trowel is held. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.

#### Installation:

All solid wood, engineered wood & bamboo, pre-finished or unfinished, all thicknesses:

Moisture inhibitor & wood installation one-step application:

Dry-back parquet:

GenieMat to approved substrate:

#### Trowel Size\* & Notch:

5 mm x 6.5 mm x 12.5 mm  
Flat V

5 mm x 6.5 mm x 12.5 mm  
Flat V with Spacers

3 mm x 3 mm x 3 mm Sq.

1.5 mm x 1.5 mm x 1.5 mm Sq.

#### Coverage:

5.5-6.5 m²/gal

3-3.5 m²/gal

5.5-6.5 m²/gal

Up to 11 m²/gal

#### QUANTITY:

Tub: 15.1 L (4 gal)

#### DENSITY:

Max. 1.2 kg/L (10.2 lb/gal)

#### LEAD TIME:

2-3 weeks after receipt of order

### TECHNICAL DATA

#### PERCENT VOLATILE:

0%

#### VOC CONTENT:

<0.50 grams/L

#### APPLICATION TEMPERATURE:

15 - 30°C (60 - 85°F)

#### APPLICATION RELATIVE HUMIDITY:

30% - 65%

#### FREEZE/THAW STABILITY:

Stable to -12°C (10°F)

#### RELATIVE HUMIDITY TEST (ASTM F2170):

Maximum 75%

Maximum 90% when used as moisture inhibited system, as per above\*

#### CALCIUM CHLORIDE TEST (ASTM F1869):

Maximum 3 lb/1000 ft²/24 hrs

Maximum 10 lb/1000 ft²/24 hrs when used as moisture inhibited system, as per above\*

\*When trowel with spacers used per moisture inhibitor system above.

## CONTACT Us

For Your Project Specific Questions

**Middle East** +971 4 813 5501 | **UK** +44 203 9846444 | **Asia Pacific** +65 8452 6865

**E.** info@pliteq.ae

© Pliteq Building Materials Trading LLC. 2020.

®™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



[www.pliteq.ae](http://www.pliteq.ae)